

Product Datasheet model super f OTG CR 9169 500

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

**Autoclavable safety
eyewear
that makes the
difference**

- Professional protection of products and humans for medical and pharmaceutical industries
- First autoclavable protective overspec with anti-fog effect
- Sterile eye protection in every situation
- Autoclavable 20 times, 121°C, 20 minutes
- Innovative design for maximum functionality and wearer comfort
- Overspecs with unrestricted lateral vision
- Also suitable for use over prescription spectacles
- Non-allergenic material which is free of harmful substances
- Ultra-modern lens technology
- Extremely flexible soft ear pieces

Product characteristics

- Lightweight overspec with unrestricted lateral vision
- XST side arms for increased comfort and pressure-free fit
- Antifog coating inside
- Lens inclination of 11° ensures good view downwards and provides the wearer from accidents caused by stumbling
- Suitable for cleanroom environments
- Optical class 1
- Particularly suitable for combination with other PPE (e.g. face masks)
- UV 400 protection

Sterilisation

Suitable for autoclave sterilization. Minimum of 20 times, at 121°C for 20 minutes After 20 cycles, the goggle shall be replaced.

Disinfection

Commercially available disinfectants can be used, either by spraying or wiping. Goggles should not be placed in disinfectant for an extended period of time.

Technical details

Frame

Material
Colour


Front piece

PA
white

Material
Colour

Temple end

PA/TPE
white, light blue

Manufacturer's ID code	Marking W
Applicable EN norm	166
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperatures	T
Conformity symbol	CE
Lens	
Material	PC
Thickness	2.1 mm
Coating	uvex supravision clean
Colour	clear
UV protection	UV400
Filter	
Filter	Marking 2C-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperatures	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Factory symbol	

Miscellaneous

Weight

37 g

Packing

5 spectacles per box

160 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 169

PPE Category

Category II